

3410 Q1® Contractor Grade Masking Tape

Q1® Contractor Grade is characterized by a regular crepe paper backing and a natural rubber resin adhesive. Universal and versatile, it is suitable for indoor masking professional applications in Painting and Building industry, and for non-critical spray painting activities at moderate temperature. No UV exposure recommended



Features

- Medium adhesion
- Good holding power
- Clean removal in warm environments without breaking
- Good contact on multiple surfaces
- Good paint anchorage
- Indoor removal time: 3 Days

Available Colour

Yellow

Product Reference

Part#	Size	Pcs/ Case
Q1CG124	24mm X 50m	36 pcs/ case
Q1CG136	36mm X 50m	24 pcs/ case
Q1CG148	48mm X 50m	20 pcs/ case
Q1CG172	72mm X 50m	12 pcs/ case

Technical Data Sheet

Characteristics	Metric	Imperial Units	Test method
Total Weight	80 g/m ²	80 g/m ²	ISO 536CE Certification
Total Thickness	110 µm	4.3 mils	Internal Method
MD tensile strength	37 N/cm	20.8 Lbs/in	AFERA 5004/PSTC 131
MD elongation at break	7%	7%	AFERA 5004/PSTC 131
Adhesion to steel plate	1.9 N/cm	17.1 oz/in	AFERA 5001/PSTC 101
Service Temperature up to	55°C	131°F	



Premium Masking Solutions

Additional Information**Technical Information and Product Use**

All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. Figures shown refer to average values only, based on tests carried out in conditioned laboratory and are not valid for specification. The company reserves the right to modify or change the products at any time without notice. The accuracy or completeness of such information is not guaranteed. The technical information, suggestions and other statements contained in this document have been compiled for your guidance and usage. PPM Industries reminds the user of the products to make sure that the product is used as per the instructions and suggestions provided. It is the user's sole responsibility to determine the suitability of the product in actual application under specific conditions.

Storage and Shelf Life

Suggested storage in dry area away from direct sunlight temperature should range from 59°F / 15°C to 77°F / 25°C with max relative humidity of 50%. Tape and jumbo roll should be used respectively within 12 months and 6 months from date of manufacture. PPM Industries does not take responsibility for the defective material if is not stored and used in accordance with the conditions listed above.